

TA-BVS 240/243



Balancing valves
Stainless steel



Engineering
GREAT Solutions

TA-BVS 240/243

A stainless steel balancing valve that delivers accurate hydronic performance in an impressive range of applications. The TA-BVS is available with flanges or welding ends and is ideal for use mainly on industrial applications and for high temperature.



Key features

- > **Handle**
Equipped with a removable handle that ensures accurate and straightforward balancing.
- > **Stainless steel**
For high media resistance and longer valve lifetime.
- > **Measuring points**
For simple, accurate balancing.

Technical description

Application:

Heating and cooling systems

Functions:

Balancing
Pre-setting
Measuring
Shut-off

Dimensions:

DN 15-250

Pressure class:

Valve body:

DN 15-50: PN 40

DN 65-250: PN 25

Flanges:

DN 15-50: PN 40

DN 65-250: PN 16

(PN 10, 25 and 40 on request)


Temperature:

Max. working temperature: 200°C

Min. working temperature: -30°C


TA-BVS 240

Note! Not for steam.



TA-BVS 243

Note! Not for steam.



- 1) Body
- 2) Flanges

Material:

Valve body: Stainless steel EN X2CrNiMo17-12-2 (1.4404) (EN 10217-7)
Ball: Stainless steel EN X2CrNiMo17-12-2 (1.4404)

Spindle: Stainless steel EN X2CrNiMo17-12-2 (1.4404)
Spindle seal: FPM (viton) and NBR (nitrile)
Ball seal: Hardened PTFE
Handle: DN 15-150 stainless steel, DN 200-250 manual gear.
Measuring points: Stainless steel EN X2CrNiMo17-12-2 (1.4404)

Marking:

Body and flanges: Traceability No.
Label on body: TA, DN, PN, CE (according to table), material, max. temperature, product No and flow direction arrow.


Marking	PN 40	PN 25
CE 0575*	DN 40-50	DN 65-250

*) Notified body.

Flanges:

EN 1092-1, ISO 7005-1.

Operating instruction




1. Locking screw
2. Measuring points
3. Removable handle
4. Two O-rings. The upper can be replaced during operation.
5. Ball with W-port. Equal percentage valve characteristic.


Measuring accuracy

Deviation of flow at different settings

The curve is valid for valves with normal pipe fittings. Try also to avoid mounting taps and pumps, immediately before the valve.



*) Setting.



Sizing

When Δp and the design flow are known, use the formula to calculate the Kv value or use the diagram.

$$Kv = 0,01 \frac{q}{\sqrt{\Delta p}} \quad q \text{ l/h, } \Delta p \text{ kPa}$$


$$Kv = 36 \frac{q}{\sqrt{\Delta p}} \quad q \text{ l/s, } \Delta p \text{ kPa}$$

Kv values

Setting	DN											
	15/20	25	32	40	50	65	80	100	125	150	200	250
1	-	-	0,39	0,60	1,26	2,52	3,42	6,48	8,6	13,7	19,7	35,0
1,5	-	0,35	0,57	1,01	1,80	3,64	5,37	9,47	13,3	20,2	20,2	51,2
2	0,14	0,49	0,83	1,48	2,70	4,75	7,31	12,5	18,0	26,6	38,4	66,5
2,5	0,28	0,99	1,08	2,02	3,55	6,34	10,2	16,3	24,3	35,5	51,1	90,0
3	0,42	1,36	1,44	2,70	4,39	7,92	13,1	20,1	30,6	44,3	63,8	110
3,5	0,61	1,66	1,80	3,24	5,61	9,78	16,1	24,5	37,8	55,1	79,3	140
4	0,80	2,00	2,30	3,96	6,84	11,6	19,1	28,8	45,0	65,9	95,0	165
4,5	1,02	2,40	2,74	4,86	8,34	14,2	23,3	35,8	55,3	84,1	121	215
5	1,24	3,00	3,42	5,98	9,83	16,7	27,5	42,8	65,5	102	147	260
5,5	1,64	3,50	4,21	7,18	11,9	20,9	33,2	51,8	81,7	127	183	325
6	2,04	4,50	5,11	8,57	14,0	25,2	38,9	60,8	97,9	152	219	380
6,5	2,64	5,10	5,97	10,2	16,9	29,5	46,3	75,4	122	197	282	500
7	3,24	6,70	7,27	12,3	19,8	33,8	53,6	90,0	146	241	325	576
7,5	3,84	7,30	8,64	14,4	23,4	39,8	64,6	113	177	290	417	740
8	4,45	9,30	10,1	17,6	27,0	45,7	75,6	137	209	338	486	866
8,5	5,04	10,0	11,5	20,9	30,6	53,5	91,8	169	251	400	576	1020
9	5,83	12,6	13,1	22,6	34,2	61,2	108	216	294	461	660	1170


Setting

DN 15-150



1. Adjust to the desired position (1).
2. Open the locking screw of the limiter (2).
3. Move the limiter against the edge of the scale plate (3).
4. Tighten the locking screw of the limiter (2).

DN 200-250



1. Adjust to the desired position (1).

Diagram DN 15-20




Diagram DN 25




Diagram DN 32




Diagram DN 40




Diagram DN 50




Diagram DN 65




Diagram DN 80




Diagram DN 100




Diagram DN 125




Diagram DN 150




Diagram DN 200






Diagram DN 250



TA-BVS 240 – Welding ends




Welding ends

DN	D	L	L1	H	Kvs	Kg	EAN	Article No
PN 40								
15	21,3	230	140	100	5,83	0,9	6415840183815	6-52 240-015
20	26,9	230	140	100	5,83	0,9	6415840183822	6-52 240-020
25	33,7	230	150	100	12,6	1,1	6415840183839	6-52 240-025
32	42,4	260	150	100	13,1	1,3	6415840183846	6-52 240-032
40	48,3	260	190	105	22,6	2,1	6415840183853	6-52 240-040
50	60,3	300	190	110	34,2	2,6	6415840183860	6-52 240-050
PN 25								
65	76,1	300	280	165	61,2	4,3	6415840183877	6-52 240-065
80	88,9	300	280	175	108	5,2	6415840183884	6-52 240-080
100	114,3	325	280	190	216	7,2	6415840183891	6-52 240-090
125	139,7	325	420	210	294	11,5	6415840183907	6-52 240-091
150	168,3	350	600	230	461	16,4	6415840183914	6-52 240-092
200*	219,1	400	-	-	660	36,0	6415840183921	6-52 240-093
250*	273,0	530	-	-	1170	71,0	6415840183938	6-52 240-094

*) Equipped with manual gear.

Kvs = m³/h at a pressure drop of 1 bar and fully open valve.

TA-BVS 243 – Flanged



Flanged

DN	Number of bolt holes	D	L	L1	H	Kvs	Kg	EAN	Article No
PN 40									
15	4x14	95	250	140	100	5,83	2,2	6415840116813	6-52 243-015
20	4x14	105	250	140	100	5,83	2,6	6415840116820	6-52 243-020
25	4x14	115	250	150	100	12,6	3,1	6415840116837	6-52 243-025
32	4x18	140	280	150	100	13,1	4,7	6415840116844	6-52 243-032
40	4x18	150	280	190	105	22,6	5,9	6415840116851	6-52 243-040
50	4x18	165	320	190	110	34,2	7,6	6415840116868	6-52 243-050
PN 16									
65	8x18	185	320	280	165	61,2	9,8	6415840116875	6-52 243-065
80	8x18	200	320	280	175	108	11,3	6415840116882	6-52 243-080
100	8x18	220	350	280	190	216	15,0	6415840116899	6-52 243-090
125	8x18	250	350	420	210	294	22,0	6415840116905	6-52 243-091
150	8x22	285	370	600	230	461	30,4	6415840116912	6-52 243-092
200*	12x22	340	425	-	-	660	51,0	6415840116929	6-52 243-093
250*	12x26	405	550	-	-	1170	100	6415840116936	6-52 243-094

*) Equipped with manual gear.

Kvs = m³/h at a pressure drop of 1 bar and fully open valve.

