

## Automatic dirt separator Zeparo G-Force SG DN 65-300 PN16

Version Dirt, Cyclone design, for heating and cooling water systems.

Antifreeze additive up to 50%.

Unique cyclone technology with up to 9 times better separation performance than conventional systems.

Separation of particles with a minimum size of 5µm.

Efficiency increases with increasing flow rate.

No clogging as with filters. Secluded dirt is collected and separated in the separation chamber.

Prepared to mount a magnetic rod.

Horizontal and vertical mounting.

Desludging valve with cap for connecting a hose can be mounted in 4 positions

Connections:	Welding and grooved ends
Housing:	Steel. Colour beryllium
Max. Pressure:	16 bar
Max. Temperature:	110°C
Min. Temperature:	-10°C
Producer:	IMI Pneumatex

**Type:** Zeparo G-Force SG DN 65 PN16  
Art. No. 313 4124 1000

Type: Zeparo G-Force SG DN 80 PN16  
Art. No. 313 4124 1100

**Type:** Zeparo G-Force SG DN 100 PN16  
Art. No. 313 4124 1200

**Type:** Zeparo G-Force SG DN 125 PN16  
Art. No. 313 4124 1300

**Type:** Zeparo G-Force SG DN 150 PN16  
Art. No. 313 4124 1400

**Type:** Zeparo G-Force SG DN 200 PN16  
Art. No. 313 4124 1500

**Type:** Zeparo G-Force SG DN 250 PN16  
Art. No. 313 4124 1600

**Type:** Zeparo G-Force SG DN 300 PN16  
Art. No. 313 4124 1700

Engineering  
GREAT  
Solutions

 IMI PNEUMATEX

 IMI TA

 IMI HEIMEIER