



Certificate number: 2111703 (1)

Issued 01/11/2021

Expires 01/11/2026

Kiwa Regulation 4 (KUKreg4) Certification

Evaluation Guideline – Kiwa UK – EG004 – Regulation 4(1)(a)

Model number(s) – see Appendix

IMI Hydronic Engineering.

Kiwa Watertec declares that legitimate confidence exists in the products specified in this certificate and supplied by the above organisation be relied upon to comply with the Kiwa Evaluation Guideline referred above.

Which verifies the requirements of:

Regulation 4(1)a of the Water Supply (Water Fittings) Regulations 1999 England & Wales: 2009 Northern Ireland and 2014 Byelaws Scotland.

This certificate has been issued in accordance with the Kiwa regulations for product certification.

Signed on behalf of Kiwa Watertec

David Jay, Business Unit Manager – Authorised Signatory
Kiwa Watertec

Publication of this certificate is allowed.

Products are intended to be used in the UK only. For other countries, other (National) requirements will apply.

See <https://www.kiwa.com/gb/en/about-kiwa/water-products/> to ensure that the certificate is still valid.

CERTIFICATE

Kiwa Watertec
(A Trading Division of Kiwa Ltd)
26A Rassau Industrial Estate
Ebbw Vale
Gwent
NP23 5SD
United Kingdom
T +44 (0)1495 308185
uk.water@kiwa.com
www.kiwa.co.uk

Certificate Issued to:
IMI Hydronic Engineering
SE-524 80 Ljung
SWEDEN



Product Certificate

Appendix to Certificate number: 2111703

The following products belong to this certificate

<p>PRODUCT DESCRIPTION Range of thermostatic circulation valves with brass bodies and EDPM O-rings. ATS3 – Without Production Surveillance.</p>
<p>MODEL(S) 52 820-015 TA-THERM-ZERO DN15 W. THERMOMETER +55°; 52 820-020 TA-THERM-ZERO DN20 W. THERMOMETER +55°; 52 820-115 TA-THERM-ZERO DN15 W/O THERMOMETER +55°; 52 820-120 TA-THERM-ZERO DN20 W/O THERMOMETER +55°; 52 820-815 TA-THERM-ZERO DN15 W. PT-PORT +55°; 52 820-820 TA-THERM-ZERO DN20 W. PT-PORT +55°.</p>
<p>SIZE: See model.</p>
<p>SCOPE: Supplier recommended maximum working pressure 16 Bar & maximum operating temperature 65°C. Hygienic Purposes: Non-metallic materials suitable for continuous use up to 65°C. Above ground use only.</p>
<p>MARKING On body: TA, PN16, DN, CR, Zero, flow direct arrows. Adhesive label on handwheel: Temperature °C, TA.</p>
<p>MATERIALS Non-metallic materials assessed (BS6920) to point of discharge.</p>
<p>BACKFLOW PROTECTION NOTES N/A.</p>
<p>ADDITIONAL NOTES All water contact & exposed components satisfy opacity requirements.</p>

Extra Notes