







Dynacon Eclipse




2	9340-02.800
3	9340-03.800
4	9340-04.800
5	9340-05.800
6	9340-06.800
7	9340-07.800
8	9340-08.800
9	9340-09.800
10	9340-10.800
11	9340-11.800
12	9340-12.800



IMI Hydronic Engineering Deutschland GmbH • Völlinghauser Weg • DE 59597 Erwitte
Tel.: +49 (0)2943 891-0 • climatecontrol.imiplc.com



Auto.



	I	4	I	I	10	I	I	I	I	20	I	I	I	I	30
I/h	30	40	60	80	100	120	140	160	180	200	220	240	260	280	300

Q [W]	200	250	300	400	500	600	700	800	900	1000	1200	1400	1600	1800	2000	2200	2400	2600	2800	3000	3200	3400	3600	3800	4000	4800	5200	
Δt [K]																												
5	3	4	5	7	9	10	12	14	16	17	21	24	28															
8			3	4	5	7	8	9	10	11	13	15	17	19	22	24	26	28										
10				3	4	5	6	7	8	9	10	12	14	16	17	19	21	22	24	26	28	29						
15					3	3	4	5	5	6	7	8	9	10	12	13	14	15	16	17	18	20	21	22	23	28	30	

Δp min. 30 - 150 l/h = 17 kPa
Δp min. 150 - 300 l/h = 25 kPa

We reserve the right to introduce technical alterations without previous notice.